



3CEMR

3 Channel External Multitek Receivers (with antenna)

The 3 Channel External Multitek Receiver (with antenna) is diverse, reliable and compatible with Dyno Code Hopping Transmitters. All you ever wanted in a receiver and more!

Features:

Each channel can be selected between pulse and latch

Each channel has a 5 amp, 220 volt output relay

Built in field strength LED to assist with installation

Unique advanced interference reduction circuit

Incorporates Multitek Smart Memory

Compatible with Binary, Trinary, French Rolling Code & Code Hopping



3CEMR

3 Channel External Multitek Receivers (with antenna)

Dimensions:

Length: 8.5cm / 11cm

Width: 8.5cm / 8.5cm

Depth: 2.8cm / 2.8cm

Antenna : 30 cm

Specifications:

TOTAL CURRENT CONSUMPTION:

6 mA + 70mA/relay

STANDBY CURRENT CONSUMPTION:

8 mA

SENSITIVITY:

1 uV

SUPPLIED VOLTAGE:

9 15V DC in Latch Mode and

9 24 AC or DC in Pulse Mode

RELAY CONTACTS:

5 amp

RELAY CONTACTS VOLTAGE:

220V AC

FREQUENCY:

403.55 Mhz

433.92 Mhz

and others on request



Tel: +27 (0)11 396 2720 / 0861 BARTRON

Fax: +27(0)11 396 2727

Web: www.bartronics.co.za

38 Pomona Road, Pomona Estates, Kempton Park

GPS Co-ordinates: S 26 05.362 E 28 16.407

P.O. Box 12188

Aston Manor

1630

South Africa